



Solar LED Flood Lamp Specification



Feature

- LED source long service life
> 50000h(5.7years)
- Lithium iron phosphate recycle
Life > 2000times(5.5years)
- Highly reliable and safe

RoHS **CE**



1.1 Product introduction

LED light source, long service life, with light control + time control for light start and close automatically.

The products can be customized individually.

1.2 Specification



SN	Product picture	Type	QTY	Unit	Parameter
1		100W	1	set	control mode : Light control + remote control +5 m wire Panel size:530*350mm Panel : Poly-Si (6V/25W) Lamp beads:200beads IP Rating : IP65 Charge mode : Solar charge Lighting time : Sustainable lighting for about 15 hours Illumination area: 150m2 Carton size : 660*415*170mm Total weight:6.2kg Battery capacity : 30000mAh Lamp size : 328*275*90 mm
2		200W	1	set	Control mode : Light control + remote control +5 m wire Panel size:700*350mm Panel : Poly-Si (12V/35W) Lamp beads:400beads IP Rating : IP65 Charge mode : Solar charge Lighting time : Sustainable lighting for about 15 hours Illumination area: 250m2 Carton size : 760*415*170mm Total weight:7.2kg Battery capacity : 36000mAh Lamp size : 360*290*90mm
Warranty					
2years					